

# EstiLo

**A New Breed of System  
for POS and hospitality**

IT-6000



**BIRCH<sup>®</sup>**

# Look beyond and See possibility.

**Comes from European creative  
concepts... "ESTILO"**

« ESTILO »... THE MASTERPIECE WHICH IS WITH EXTREMELY  
BEAUTIFUL BOUNDARY

IN SPANISH, THE ESTILO REFERS TO THE BEST QUALITY  
SCULPTURE PRODUCE BY WAY OF "DELICATE WORK".

WE COMBINE THE CREATIVITY, UP-TO-DATE TECHNOLOGY  
AND USER'S INTERFACE TO CREATES THE ESTILO PC THAT  
BRING THE CUSTOMERS' UPMOST SATISFACTION  
AND CONVENIENCE WHICH WE ALWAYS PURSUE.







# Elegant & Superior



## IT-6000 Structure

### + ESTILO IT-6000 UNIQUE STREAMLINED OUTLOOK DESIGN

BASED ON THE HUMAN MOST COMFORTABLE VIEWING VISION ANGLE, "L" SHAPE DESIGN MATCHES THE TECHNOLOGY AND THE INNOVATION TO MAKE IT-6000 TO BE CONCISE POWERFUL PRODUCT.

### + ALUMINIUM HOUSINGS AND 5-WIRE RESISTIVE TOUCH TECHNOLOGY

TO ASSURE THE HIGH-END PERFORMANCE AND HIGH-TECH, IT-6000 IS MADE OF ALUMINIUM AND BUILT-IN AU TFT LCD AND 5-WIRE RESISTIVE TOUCH SCREEN(10.4" TFT LCD AS STANDARD, OPTIONAL FOR 12.1" TFT).

### + HIDEAWAY TO BUCKLE CABLE CONNECTION

ALL PERIPHERAL CABLES SUCH AS PRINTER IS FIRMLY CONNECTED TO THE BUCKED TYPE DESIGN HIDDEN INSIDE THE HOUSING. IT-6000 COMES WITH 2 X SHORT CONVERTED CABLE AS STANDARD (OPTIONAL FOR MORE CABLES).



### + FOR USER FRIENDLY APPLICATIONS, USB AND AUDIO CONNECTOR ON THE SIDE OF IT-6000.

--OPTIONAL FOR IButton.

--OPTIONAL FOR MAGNETIC CARD READER AND CUSTOMER  
DISPLAY( COMING SOON).





## BETWEEN THE LINES

### + OPERATION SOFTWARE SUPPORTED

IT-6000 BUILT-IN 5-WIRE ANALOG RESISTIVE TOUCH CONTROLLER WHICH SUPPORTS MS WINDOWS XP/2000/95/98/ME, WINDOWS NT4.0/CE 2.212/3.0/NET, DOS, LINUX REDHAT, LINUX MANDRAKE, MAC/OS 9... ETC.

### + INDUSTRIAL PC MOTHERBOARD STANDARD

IT-6000 BUILT-IN HIGH-END INDUSTRIAL PC M/B STANDARD WHICH IS UNDER STRICT-QUALITY CONTROL SYSTEM AND ISO STANDARDS.

### + CPU RANK BY CELERON

BUILT-IN STYLISH COOL-RUNNING CELERON-M CPU TO PROVIDES HIGH PERFORMANCE AND RELIABILITY.

CELERON-M 600/800 MHZ AS STANDARD  
(OPTIONAL FOR CELERON 1.3MHz).

### + HEAT SINK

BESIDES USING COOL-RUNNING CPU, IT-6000 HAS THE ALUMINUM MATERIALS AND SPECIAL DESIGN HEAT SINK FOR FAST RADIATION OF HATING.

### + MORE FEATURES.....

1. INTEL 852GME + ICH 4
2. SUPPORTS DUAL VIEW ON SECOND VGA.
3. OPTIONAL FOR CF OR DOM( UP TO 4 GB)
4. OPTIONAL FOR 6 CHANNEL SURROUNDING AUDIO 5.1





#### CPU

---

- + ULV CELERON-M 600MHz (OPTION 1.3GHz) BASED INDUSTRIAL GRADE SUB-COMPACT BOARD
- + 256MB DDR SODIM RAM (UPGRADE UP TO 1GB)
- + CHIPSET: INTEL 852GME + ICH4
- + SUPPORTS DUAL VIEW ON SECOND OPTIONAL TFT
- + ETHERNET: INTEL 82562 (10/100MHz)

#### DISK

---

- + HDD 2.5" 40GB (OR HIGHER) OR FLASH DOM UP TO 4GB.
- + OPTIONAL CF, OPTIONAL DOM.

#### DISPLAY & TOUCH

---

- + 10.4" TFT AS STANDARD (OPTIONAL FOR 12.1" TFT)
- + 230 Cd. (Nits) HIGH BRIGHTNESS TFT.
- + 5-WIRE RESISTIVE TOUCH.

#### I/O's

---

- + 6 SERIAL COM
- + 3 USB 2.0
- + 10/100 MHz LAN
- + 6 CHANNEL SURROUND AUDIO (5.1) (OPTION)
- + WiFi AND MODEM OPTION THRU MINI-PCI CONNECTOR
- + AC97 AUDIO I/O (STANDARD).
- + PS/2 KBD
- + VGA

#### PHYSICAL PARAMETERS

---

- + POWER INPUT: 12 VDC
  - + POWER CONSUMPTION: 20 W
  - + DIMENSIONS (MM): 240 x 240 x 200 (HEIGHT)
  - + OPERATING TEMP: 0-60 DEG.
-