NEW

mini Ó II

10” monitor, sensible and unique all in one total-solution POS system

System

mini O II	
CPU	Intel Atom N270 1.6GHz processor
Chipset	Intel 945GSE+ICH7M
HDD	1GB SSD (HDD option)
Memory	DDR2 SODIMM x 1 slot (Default 1GB up to 2GB)
VGA	Intel 945GSE GMA950 Engine
Printer	2” thermal printer (200mm/sec max, Auto cutter)
Display	10” (1024 x 768)
External I/O	
USB	Side 1, Rear 2
RS-232	COM 1 ~ 2 with + 5 / 12V power output on 9pin
LAN	GbE LAN
Cash drawer	1 x RJ11 , Cash drawer port
Options	
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track
SCR	IC card reader
Dallas	Dallas I-button reader
Keyboard	Mini standard keyboard or Programmable keyboard : 55 Key
Customer display	Real or Pole type customer display
CF CARD	CF card reader
Power Supply	INPUT : 100-240V~, 50/60Hz 1.5A OUTPUT : DC24V 2.5A
OS Support	Windows CE 6.0 on SSD, Windows XP/XPE, POS Ready (WEPOS) on HDD, Linux

* Product is applied locally with different specifications and is also capable of being altered without prior notice.